

## **P.J. Grady Inc.**

P.O. Box 7(mail) or 118 Montauk Hwy

West Sayville, NY 11796

(516)589-8224 Tech - 800-350-7429 Parts - (518)589-8241 Fax

### **TRAILING ARM SHIELD BRACKET KIT**

P/N 110811G

This retaining bracket kit allows fast and easy removal of your DeLorean's trailing arm shields to check trailing arm pivot bolt/bushing retention and condition or to allow rear suspension toe - in adjustments. The stock fasteners tend to corrode and seize together, making shield removal a time consuming chore. One piece all stainless construction of these brackets allows Immediate access to this "safety critical" area of your Delorean.

This installation is simple, provided the original fasteners have not seized together. If the studs are frozen or you need trailing arm service or alignment adjustments, it is advisable to use a professional mechanic who has the recommended tools. After the kit is installed only a 10mm wrench is necessary for T.A. shield removal.

### **TOOLS REQUIRED**

10mm Box Wrench or 10mm Socket with Ratchet Wrench  
Silicone Adhesive (3m, GE, Etc.)

### **RECOMMENDED ADDITIONAL TOOLS**

3/8" Pneumatic Impact Gun  
Pneumatic Muffler Clamp Cutter  
1/4" Power drill (pneumatic or electric)  
1/8 Drill Bit  
Rivet Gun

### **INSTALLATION INSTRUCTIONS**

- (1)** Remove battery and rubber pad from R/H battery compartment door and remove 10mm rivets securing T.A. shields, and remove shields. If fasteners spin, have assistant (in the car) stop the studs from turning, using a suitable tool (channel lock, screwdriver, etc.). If this procedure fails, it will be necessary to cut off the studs with a hacksaw, pneumatic muffler clamp cutter, etc. Remove studs.
- (2)** Apply 1/8" bead of silicone adhesive along bracket and around studs and place into position. If you have a drill and rivet gun, use predrilled holes (two) in the bracket as a guide to drill through the fiberglass body pan and install supplied rivets. If you do not use the rivets, allow silicone to cure before installing T.A. shields.
- (3)** Reinstall battery, storage compartment, carpet and respective covers. Position T.A. shields and secure with supplied stainless locknuts and washers.